

304 Stainless Steel Circular Groove Top Hung Friction Hinge For Aluminum Window

Our Product Introduction

for more products please visit us on aluminum-windowhardware.com

Basic Information

- Place of Origin: China
- Brand Name: XuanQing
- Model Number: SH-113
- Minimum Order Quantity: 500PCS
- Price: Negotiable
- Packaging Details: Carton Box
- Delivery Time: 10-15 work days
- Payment Terms: T/T
- Supply Ability: 3000000pcs/mon



Product Specification

- Warranty: 3 Years
- After-sale Service: Online Technical Support, Onsite Training, Other
- Project Solution Capability: Graphic Design, Total Solution For Projects, Others
- Application: All The Scenarios
- Design Style: Modern
- Type: Friction Stay
- Highlight: **Circular Groove Top Hung Friction Hinge, Stainless Steel Top Hung Friction Hinge, Window Top Hung Friction Hinge**



More Images



Product Description

304 Stainless Steel Circular Groove Top Hung Friction Hinge For Aluminum Window

Product Attributes

Attribute	Value
Warranty	3 years
After-sale Service	Online technical support, Onsite Training, Other
Project Solution Capability	graphic design, total solution for projects, Others
Application	All the scenarios
Design Style	Modern
Type	Friction stay

Product Description

The top hung aluminum window's 304 stainless steel circular groove friction stay is designed for all scenarios. Made of durable and corrosion-resistant 304 stainless steel, it offers a stable fit for the window. Specifically for top hung aluminum windows, it supports the weight and controls opening and closing. The circular groove design ensures smooth operation and prevents sudden movements. With enhanced durability, it can withstand heavy use. Versatile for different settings, it provides a reliable solution. Ideal for residential, commercial, and industrial applications.

Quick Details

Material: 304 stainless steel, known for durability and corrosion resistance.

For: Top hung aluminum windows.

Design Feature: Circular groove for stability.

Function: Supports window, controls opening and closing.

Benefits: Smooth operation, enhanced durability, suitable for all scenarios.

Specification

13.5 Square slot raised four-link stainless steel upper suspension brace hinge series Installation dimension (unit :mm)

specification	A	B	E	F	G	H	I	J	K	L	M	N
10"	258	251		145	44	30	200	190	112	58	38	
12"	301	293	210	181	44	30	175	135	58	38		
14"	348	339	222	193	44	30	202	160	58	38		
16"	402	394	227	198	44	30	236	195	60	42		
18"	454	445	222	193	44	30	256	216	58	38		
20"	499	490	260	231	44	30	298	246	58	38		
22"	551	542	268	239	44	30	329	287	216	93	58	38
24"	598	589	274	245	44	30	373	331	249	135	60	42

specification	Maximum window height (mm)	Maximum window width (mm)	Material weight (kg)	Opening Angle
10"	900	400	20	±87°
12"	900	500	25	±87°
14"	1000	600	28	±87°
16"	1200	700	30	±87°
18"	1200	800	35	±87°
20"	1200	900	38	±87°
22"	1200	1000	42	±87°
24"	1200	1200	45	±87°



Company Profile



SOME HONORS



宣清智连科技
Xuanqing Zhilian Technology

Foshan Xuanqing Zhilian Technology Co., LTD



+8613827792344



fsxuanqing@gmail.com



aluminum-windowhardware.com

Guangdong Foshan Nanhai No. 5-1, Songgang Lianbiao Industrial Zone, Shishan Town